

extra

Panel Radiators




EXTRA Panel radiators:

- Radiators design and the architecture which being inspired satisfy each modern view and opinion. A big range of types covers every necessity for heating in new or old places such as buildings, industrial places, offices etc.
- Radiators are manufactured in a fully automatic production process according the specifications of European Union.




extra

Length [mm]	Type		11		22			33		
	Units	Height	600	900	500	600	900	500	600	900
400	Kcal/h		469	656	686	868	1191	1058	1293	1810
	Watt		543	759	794	1005	1378	1225	1497	2095
500	Kcal/h		587	820	858	1085	1489	1322	1617	2263
	Watt		679	949	993	1256	1723	1530	1872	2619
600	Kcal/h		704	983	1029	1302	1787	1586	1940	2716
	Watt		815	1138	1191	1507	2068	1836	2245	3144
700	Kcal/h		821	1147	1201	1519	2085	1851	2263	3168
	Watt		950	1328	1390	1758	2413	2142	2619	3667
800	Kcal/h		938	1311	1372	1736	2382	2115	2586	3621
	Watt		1086	1517	1588	2009	2757	2448	2993	4191
900	Kcal/h		1056	1475	1544	1953	2680	2380	2910	4073
	Watt		1222	1707	1787	2260	3102	2755	3368	4714
1000	Kcal/h		1173	1639	1715	2170	2978	2644	3233	4526
	Watt		1358	1897	1985	2512	3447	3060	3742	5238
1100	Kcal/h		-	-	1887	2387	3276	2908	3556	4979
	Watt		-	-	2184	3457	3792	3366	4116	5763
1200	Kcal/h		-	-	2058	2604	3574	3173	3880	5431
	Watt		-	-	2382	3014	4137	3672	4491	6286
1400	Kcal/h		-	-	2401	3038	4169	3702	4526	6336
	Watt		-	-	2779	3516	4825	4285	5238	7333
1600	Kcal/h		-	-	2744	3472	4765	4230	5173	7242
	Watt		-	-	3176	4019	5515	4896	5987	8382
1800	Kcal/h		-	-	3087	3906	5360	4759	5819	8147
	Watt		-	-	3573	4521	6204	5508	6735	9429
2000	Kcal/h		-	-	3430	4340	5956	5288	6466	9052
	Watt		-	-	3970	5023	6894	6120	7600	10477
2200	Kcal/h		-	-	3773	4774	6552	5817	7113	9957
	Watt		-	-	4367	5525	7583	6733	8233	11524
2400	Kcal/h		-	-	4116	5208	7147	6346	7759	10862
	Watt		-	-	4764	6028	8272	7345	8980	12572
2600	Kcal/h		-	-	4459	5642	7743	6874	8406	11768
	Watt		-	-	5161	6530	8962	7956	9727	13620
2800	Kcal/h		-	-	4802	6076	8338	7403	9052	12673
	Watt		-	-	5558	7032	9650	8568	10477	14668
3000	Kcal/h		-	-	5145	6510	8934	7932	9699	13578
	Watt		-	-	5955	7535	10340	9181	11110	15715



- Manufactures from steel sheet ST 1203 according DIN 1541, 1623
- Maximum operation temperature 110 °C max
- Thickness of steel sheet 1,25mm
- Testing pressure 13 bar
- Function pressure 10 bar max
- For the best heating output meander is being weld in the length of the water pipes
- Electrostatic painting
- White color RAL 9010
- Paint DIN 55900



- Panel radiators extra are delivered with faultless and durable packing which securing safety transportation:
 - Radiator is covered with strong paper (thickness 5mm) and specific nylon.

- Hangers
- End Plugs
- Screw holders
- Trifon screw
- Air vent plug
- Clips